



arvox
The 2 component cleaner

Product data sheet

Description

Arvox Pro Wood cleans wooden surfaces, decking, garden furniture and wooden facades. Removes organical soiling without attacking the surfaces. Grayed wooden surfaces are visibly refreshed. Ideal for pre-treatment for subsequent care of the wood.

Product advantages

- **Effective:** easy & fast application
- **Innovative:** active oxygen dissolves the dirt
- **Environmentally neutral:** reaction products are biodegradable
- **Clean:** without chlorine, silicones, alcohol, perfume, aldehydes

Application

Preparation: Remove loose dirt from the surface. If necessary, cover surfaces that are not to be treated. May affect metals. Test product on a less visible spot.

Manual application: Spray the surface to be cleaned thoroughly with Arvox Pro A and wet it completely. Then apply Arvox Pro B in the same way and work it in with a brush or scrubber. Rinse/rework the treated surface with water and brush after approx. 5 - 15 minutes.

Machine application: Apply Arvox Pro A and B one after the other to the wood surface with low pressure sprayers. Allow to react for approx. 5 - 15 minutes, depending on the degree of soiling. To increase the cleaning effect, brush the components with a suitable cleaning machine after application. Rinse the surface with water and, if necessary, clean after with a brush or scrubber.

Note: Apply Arvox on a dry surface. Do not use in strong sunlight or moisten the surface slightly if necessary.

Coverage: approx. 4-10m²/L (0,5 L per component)



Manual application:
The components are worked in with a brush or cleaning pad.



Machine application:
Components should preferably be applied with eccentric cleaning machines and appropriate pads. For simultaneous application we recommend the use of double tank sprayers. (Available at Arva)

Containers/Sets

Bottles incl. spray heads

2x1L

Art.Nr.: 11010303

Canisters

2x2,5L

Art.Nr.: 11010308

2x10L

Art.Nr.: 20010305





Handling and storage

Arvox Pro Wood has a shelf life of at least 24 months when stored in the original container as recommended. Store in a place accessible only to authorised persons. Store in a cool, dark and upright position. Heat as well as direct sunlight may impair the effectiveness of the product. Use up opened containers within 3 months. Use only clean spray heads or pressure sprayers. Dispose of product residues and containers in accordance with official regulations.

Safety measures

The usual safety precautions for handling chemicals should be observed. In particular, protective gloves, goggles, protective clothing and a mask should be worn. Detailed safety instructions can be found in the safety data sheets for Arvox Pro Wood A and B.



Arvox Pro Wood is particularly suitable for basic cleaning and before applying oils and varnishes.

Properties

Arvox Pro A

Contains (acc. to 1271/2008/EC) sodium hydroxide; (acc. to 648/2004/EC) not relevant.

Appearance	Clear
Colour	Colourless
Odour	Characteristic/alkaline
Density	1,052 g/cm ³
Dynamic viscosity	22 mPa.s
Boiling point	102°C
pH	13-14

Arvox Pro B

Contains (acc. to 648/2004/EC) 5% - <15% oxygen-based bleaching agent.

Appearance	Like water
Colour	Colourless
Odour	Very faint, characteristic
Density	1,026 g/cm ³
Dynamic viscosity	1,1 mPa.s
pH	3-4

Values measured at 20° C (unless stated differently).

DISCLAIMER Use Arvox Pro products at your own risk. Observe the product information and labels. Use only according to instructions. Check surface compatibility. Arva Greentech GmbH accepts no liability for any damage caused by the use of the Arvox Pro product line, including consequential damage that may result from incorrect storage or improper use of the product.



Arva Greentech GmbH
Helmholtzstr. 2-9 | 10587 Berlin | Tel.: +49 (0)30 8093341-20
contact@arvox.cleaning | www.arvox.cleaning